



RP *SeaStrike*TM
RP *SeaStrike-X*TM

variant Sea-Doo GTITM/GTXTM PWC



www.RPAMS.com
Bringing more **ASSETS** to the fight!

RP *SeaStrike*™ RP *SeaStrike-X*™

variant **Sea-Doo GTI™/GTX™ PWC**



Standard Configuration

RP SeaStrike™

- Boarding ladder
- Touring seat
- Swim platform carpet
- Variable Trim System (VTS™)
- LinQ™ attachment system (accessory)
- Naturally aspirated intake system
- Twin RP Inflated Sponsons ruggedly constructed using Thermofused™ Seam construction and Urethane Seamless Encapsulation processes

RP SeaStrike-X™

- Boarding ladder
- Tilt steering
- Watertight phone box
- Large swim platform
- Swim platform carpet
- 7.6 in wide digital display
- Variable Trim System (VTS™)
- LinQ™ attachment system (accessory)
- Supercharged external intercooler intake system
- iControl® Learning Key® allows limiting the performance of the PWC based on rider skill level
- Twin RP Inflated Sponsons ruggedly constructed using Thermofused™ Seam construction and Urethane Seamless Encapsulation processes.

RP INFLATED SPONSONS:

- Dual Sponson System with over 1000 lbs added flotation
- Integrated safety rope/grab handles
- Multiple color options
- 100% Made in the USA
- Inquire about the standalone RP Sponson Kit for your Sea-Doo unit

OPTIONAL EQUIPMENT:

- RP custom graphic wrap and color options
- Custom lighting, front and rear, LED/IR/Other
- Towable rescue sled
- Upgraded hull protection, intake grate, ceramic coatings, and more ...

VEHICLE SPECIFICATIONS

- Intelligent Throttle Control (iTC™) system
- Palm rest handle grips
- Intelligent Brake and Reverse (iBR®)
- Closed-Loop Cooling System (CLCS)
- Scratch and impact-resistant lightweight polytec hull material with added protective-abrasive-impact resistant monolithic membrane
- Anti-Theft Security System (D.E.S.S.)
- Flush mounted LED Navigation Lights
- Sealed storage: SeaStrike 30.7 US gal (116.6 L) / SeaStrike-X 27.1 US gal (102.5 L)

ENGINE	SeaStrike	Rotax® 1503 NA
	SeaStrike-X	Rotax® 1500 HO ACE™
DRY WEIGHT ¹	SeaStrike	790 lb / 359 kg
	SeaStrike-X	805 lb / 365 kg
RIDER CAPACITY	3	
WEIGHT CAPACITY	600 lb / 272 kg	
DISPLACEMENT	1,494 cc	
DIMENSIONS ² (LxWxH)	SeaStrike	132.6 x 48.5 x 44 in 336.8 x 123.1 x 111.8 cm
	SeaStrike-X	135.9 x 49.4 x 44.9 in 345.1 x 125.5 x 114 cm
FUEL CAPACITY	15.9 gal / 60 L	
HULL TYPE/ MATERIAL	SeaStrike	GTI Hull/Fiberglass
	SeaStrike-X	ST3 Hull/Fiberglass

¹ With inflatable sponson +50 lbs

² Without inflatable sponson



INFORMATION & DEALER INQUIRIES

Jim Baynes 503-348-7950, Terry Wilmeth 971-237-3217 or CustomerService@RPAMS.com



RP Advanced Mobile Systems

Veteran and Minority Owned Business

11160 SW Durham Lane, Suite 3 | McMinnville, Oregon 97128 | phone: 503-434-9446 | fax: 503-217-6080

www.RPAMS.com

All pricing, specifications, claims and information contained in this brochure are based on information available at the time of publication and are subject to change without notice. RP Advanced Mobile Systems, LLC assumes no responsibility for any inaccuracies, opinion, errors or omissions in those publications, nor fitness of purpose and non-infringement of intellectual property.

REV-09102019