



RP Strike-M™ RP Strike-M4™

variant **Can-Am Maverick DPS™/Max DPS™**



RPAMS STRIKE-M STANDARD 2018 SPECIFICATIONS

CAN-AM 1000R ENGINE | 101 HP

Type	101 Hp, 1000R Rotax® 976 cc, V-twin with high-flow dynamics, liquid-cooled. Mid-engine layout for mass centralization
Fuel Delivery System	Intelligent Throttle Control (ITC™) with Electronic Fuel Ignition (EFI)
Transmission	CVT with Zylon-reinforced belt, L / H / N / R / P, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok® QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS™)

CHASSIS

Frame	Steel
Cage Type	2-in / 5.1 cm diameter, high-strength steel, ROPS-approved
Steering Wheel Adjustment	Adjustable tilt steering
Front Suspension Type/Travel	Double A-arm with sway bar / 14 in (35.6 cm)
Rear Suspension Type/Travel	Torsional Trailing A-arm (TTA) independent with sway bar / 14 in (35.6 cm)
Shocks	Upgraded shocks for high payload operations
Front Brake	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear Brake	Dual 214 mm ventilated disc brakes with hydraulic single-piston calipers
Tires Front/Rear	RP SOF Series II, 12-PLY, Run-Flat, 26x9x12 in / 66x22.9x30.5 cm
Wheels	ITP Delta 12" steel wheels, black



WEIGHT/DIMENSIONS

Dry Weight	1,700 lb to 1,950 lb / 771.1 kg to 884.5 kg		
L x W x H (in.)	Strike-M: 129 x 64 x 74.2 in Strike-M4: 159 x 64 x 78 in	129 x 60 x 60 in with narrowing kit & retracted roll cage 159 x 60 x 60 in with narrowing kit & retracted roll cage	
L x W x H (cm)	Strike-M: 327.66 x 162.5 x 188.54 cm Strike-M4: 403.86 x 162.5 x 198 cm	327.66 x 152.4 x 152.4 cm with narrowing kit & retracted roll cage 403.86 x 152.4 x 152.4 cm with narrowing kit & retracted roll cage	
Wheelbase	Strike-M: 84.3 in / 214.1 cm	Strike-M4: 113.8 in / 289.1 cm	
Ground Clearance	Strike-M: 13 in / 33 cm	Strike-M4: 12.5 in / 31.85 cm	
Cockpit Storage	Glove box: 4.5 gal / 17.2 L	Under driver seat: 3.5 gal / 13.1 L (M only)	Center console: 0.3 gal / 1.3 L
Fuel Capacity	10 gal / 37.8 L		
Payload Capacity	Strike-M: 1,500 lb / 680 kg	Strike-M4: 2,000 lb / 907.1 kg	
Rear Cargo Bed Capacity	RPAMS Rear Bed: 1,000 lb / 453.6 kg BRP Standard Bed: 200 lb / 91 kg (Strike-M4 150 lb / 68 kg) with LinQ quick-attach		
Optional Front Rack Capacity	250 lb / 113.4 kg		
Towing Capacity	RPAMS Rear Bed: 1,500 lb / 680 kg	BRP Standard Bed: N/A	
Exterior Paint	RP Super Grit Texture Coating, Tan, Black, Camo		

RPAMS STRIKE-M STANDARD 2018 SPECIFICATIONS

ADDITIONAL FEATURES

Guage	Multifunction Digital: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, sport mode, ECO mode, seat belt and 4 x 4 indicator, diagnostics, clock, auto shut off
Anti-Theft System	Digitally Encoded Security System (D.E.S.S.™)
Electrical	Prewired for Winch
Lighting	240-W from four 60-W projectors with tail lights/brake lights
Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Exterior Accessories	High-capacity, multi-modal tactical payload flatbed, multi-modal tailgate system for multiple tactical payload track configurations, tactical assault front push bumper with strut integrated payload track system and aerial transport tie-downs, forward/rear 2" receiver, Passenger handhold and grab bar *MEDEVAC integration system - M4 ONLY
Interior	RP Fatigue Mitigation Tactical Seat System, MOLLE, 1000D Cordura®
Roof	RP Soft Roof, MOLLE, 1000D Cordura®
M4 Rear Seating	Rear seating with Best-In-Class leg room for rapid egress/ingress, fold forward for Stokes/NATO litter carriage in bed
Protection	N/A

WARRANTY

Factory	6 months limited warranty
----------------	---------------------------

RPAMS STRIKE-M OPTIONAL EQUIPMENT

RECOMMENDED OPTIONS

Exterior Accessories	High-Load tactical team standoff nerf bar/rock slider with stow and lock mode for air transport
Modular Storage	RP modular ammo/fuel can/payload assembly
Wheels	Beadlock wheels
Shocks	Elka high-performance shocks
Lighting	Baja Designs driving/blackout/IR lights & light bars
Power	Additional 12VDC & 24VDC outlets

ADDITIONAL FEATURE OPTIONS

Coating	RP Powdercoat, HydroGraphic Finishes, custom colors and patterns available
Narrowing Kit	A-arms and trailing arms
Cargo Rack	RP modular front cargo rack assembly
Cage	Quick release articulating roll cage assembly for internal aerial transport
Tires	RP SOF Series II, 12-PLY, Run-Flat, 26x9x14 in / 66x22.9x35.6 cm
Tracks	Apache 360 LT Track System and mounting kit
Drive Train	Selectable RODS (Rear Open Differential System)
Ignition	RP keyless ignition
Lighting	HID/LED light illumination
Hydration Seat	Integrated seat hydration packs
Harness	RP 4-point static harness with quick release
Communication	SatFi communication system/bundle
Accessories	Antenna mount
Windshield	Half windshield
MEDEVAC*	MEDEVAC Integration

*NOTE: Does not include litter/stretcher device. Must be purchased separately.



**RP Advanced
Mobile Systems™**

www.RPAMS.com | 503-434-9446

RPAMS STRIKE-M OPTIONAL EQUIPMENT

ADDITIONAL FEATURE OPTIONS

RP Litter System*	RP litter restraint, multi-modal and configurable rail system
Jumper	PowerAll® Jump Start System
Spare Parts Kit	Initial spare parts kit
Winch	Self-extracting 4500 lb winch

*NOTE: Does not include litter/stretching device. Must be purchased separately.



Other options may be available. Please call for more information.

INFORMATION & DEALER INQUIRIES: CustomerService@RPAMS.com



RP Advanced Mobile Systems

Veteran and Minority Owned Business

11160 SW Durham Lane, Suite 3 | McMinnville, Oregon 97128 | phone: 503-434-9446 | fax: 503-217-6080

www.RPAMS.com

All pricing, specifications, claims and information contained in this brochure are based on information available at the time of publication and are subject to change without notice. RP Advanced Mobile Systems, LLC assumes no responsibility for any inaccuracies, opinion, errors or omissions in those publications, nor fitness of purpose and non-infringement of intellectual property. All rights reserved. †Visco-Lok is a trademark of GKN Viscodrive GmbH. †All other trade marks are the property of their respective owners.

REV-07052018